

# TP 17 450

Technical data		
<b>Type</b>	TP 17 450	
<b>Control sensor</b>	Internal	
Dry block		
<b>Temperature range*</b>	RT...450 °C	RT...842 °F
<b>Accuracy</b>	±0.6 °C	±1.08 °F
<b>Stability</b>	±0.1 °C	±0.18 °F
<b>Measurement zone</b>	110...150 mm	4.3...5.91 in.
Block dimensions		
→ Diameter	Ø 60 mm	Ø 2.36 in.
→ Depth	150 mm	5.91 in.
Display unit		
<b>Display</b>	2-line, 4-digit display Red / green, unit °C / °F	
<b>Display range</b>	0...450 °C	32...842 °F
<b>Resolution</b>	0.1 °C	0.1°F
General data		
<b>Dimensions</b>		
→ Width	150 mm	5.91 in.
→ Height	330 + 70 mm	12.99 + 2.76 in.
→ Depth	270 mm	10.63 in.
<b>Weight</b>	Approx. 7.5 kg	Approx. 16.53 lbs.
<b>Power supply</b>	230 / 240 VAC, 50 / 60 Hz	
<b>Power consumption</b>	Approx. 2000 W	

\* At an ambient temperature of 20 °C / 68 °F

## Type TP 17 450



### Scope of delivery

- Test certificate
- Mains cable
- Insert exchange tool
- Operating manual

### Accessories

- Transport case
- Service transport bag
- Adapter sleeve
- DAkkS certificate
- Works certificate



The TP 17 450 temperature calibrator model has a very large calibration volume.